

NEW "DCP" 4-POST HYDRAULIC REGENERATIVE TRIM PRESS SPECIFICATIONS S-SERIES

Rev 9/15/21

Model Number	Tonnage	Platen Size TxDXW	Bore & Stroke	Dist Betw Bars	Shut Height	Daylight	Tie bar dia.	Horse power
DCP1001S	100 TON@2600 PSI	6" x 61" x 73"	10" x 42"	36" x 61"	18"	60"	5"	40
DCP751S	75 Ton @3000 PSI	5"x 38"x 62"	8" x 24"	26" x 50"	16"	40"	4"	30
DCP752S	75 Ton @2000 PSI	6"x 60"x 62"	10" x 30"	48" x 50"	16"	46"	4"	30
DCP753S	75 Ton @2000 PSI	6"x 48"x 96"	10" x 30"	36" x 72"	16"	46"	4"	30
DCP754S	75 Ton @ 2000 PSI	7" x 47" x 63"	10" x 20"	30" x 52"	16"	36"	4"	30
DCP755S	75 Ton @ 2000 PSI	6" x 42" x 60"	10" x 34"	50" X 74"	11.5"	34"	4"	50
DCP756S	75 Ton @ 3000 PSI	6" x 48" x 73"	8" x 48"	36" x 61"	18"	66"	4"	30
DCP757S	75 ton@ 3000 PSI	5" x 61" x 73"	8" x 42"	48" x 60"	18"	60"	4.5"	30
DCP758S	75 ton @ 3000 PSI	6" x 47" x 65"	8" x 24"	36" x 54"	16"	40"	4"	30
DCP759S	75 Ton @ 3000 PSI	6" x 48" x 72"	10" x 30"	36" x 60"	18"	48"	4"	30
DCP621S	62 Ton @ 2500 PSI	5"x 42"x 72"	8" x 24"	30" x 60"	15"	39"	3 ½"	30
DCP622S	62 Ton @ 2500 PSI	5" x 48" x 72"	8" x 18"	36" x 60"	20"	38"	3 ½"	30
DCP501S	50 Ton @ 2500 PSI	4"x 37"x 60"	7" x 18"	25" x 48"	14"	32"	3"	25
DCP502S	50 Ton @ 2500 PSI	4"x 42"x 50"	7" x 20	30" x 38"	14"	34"	3 ½"	25
DCP503S	50 Ton @ 2500 PSI	4 ½"x 48"x 60"	7" x 20"	36" x 48"	16"	36"	3 ½"	25
DCP504S	50 Ton @ 2500 PSI	5" x 36" x 52"	7" x 20"	26" x 42"	16"	36"	3 ½"	25
DCP401S	40 Ton @ 2100 PSI	4"x 32"x 48"	7" x 18"	20" x 36"	14"	32"	3"	20
DCP402S	40 Ton @ 2100 PSI	4"x 36"x 48"	7" x 18"	24" x 36"	16"	34"	3"	20
DCP403S	40 Ton @2850 PSI	4" x 33" x 55"	6" x 24"	24" x 46"	13"	37"	3"	20
DCP351S	35 Ton @ 2500 PSI	3.5"x 32"x 48"	6" x 16"	20" x 36"	14"	30"	3"	20
DCP352S	35 Ton @ 2500 PSI	3.5"x 36"x 54"	6" x 16"	24" x 42"	14"	30"	3"	20
DCP353S	35 Ton @ 2500 PSI	4" x 36" x 60"	6" x 24"	24" x 48"	12"	36"	3"	20
DCP354S	35 Ton @ 2500 PSI	3 ½" x 36" x 48"	6" x 24"	24" x 36"	12"	36"	3"	20
DCP355S	35 Ton@ 2500 PSI	4" x 34" x 56"	6" x 24"	24" x 46"	13"	37"	3 ½"	15
DCP301S	30 Ton @ 2200 PSI	3"x 32"x 42"	6" x 12"	20" x 30"	12"	24"	3"	20
DCP302S	30 Ton @ 2200 PSI	3"x 36"x 48"	6" x 12"	24" x 36"	12"	24"	3"	20
DCP303S	30 Ton @ 2200 PSI	4" x 39" x 46"	6" x 12"	30" x 36"	12"	24"	3"	20
DCP304S	30 Ton @ 2200 PSI	4" x 36" x 46"	6" x 18"	26" x 36"	16"	34"	3"	20
DCP305S	30 Ton @ 2200 PSI	4" x 30" x 43"	6" x 24"	19" x 33"	12"	36"	3"	20
DCP251S	25 Ton @ 2600 PSI	3"x 36"x 45"	5" x 12"	26" x 36"	12"	24"	2 ½"	15
DCP201S	20 Ton @ 2100 PSI	2.5"x 28.5" x 40.5"	5" x 12"	18" X 30"	12"	24"	2 ½"	15
DCP202S	20 Ton @ 2100 PSI	2.5"x 26"x 32.5"	5" x 12"	17" x 24"	15"	26"	2 ½"	20
DCP203S	20 Ton @ 2100 PSI	3.5" x 30.5 x 43 .5	5" x 14"	20" x 33"	14"	28"	2 ½"	15
DCP204S	20 Ton @ 2100 PSI	3" x 26" x 45"	5" x 28"	26" x 36"	12"	40"	3"	15
DCP205S	20 Ton @ 2050 PSI	3" x 38" x 29"	5" x 18"	15 ½"x 30 ½"	12"	30"	2 ½"	10
DCP151S	15 Ton @ 1600 PSI	3.5" x 30.5 x 43 .5	5" x 18"	20" x 33"	14"	32"	2 ½"	15
DCP152S	15 Ton @1600 PSI	3" x 26" x 32.5"	5" x 12"	17" x 22"	12"	24"	2 ½"	15
DCP153S	15 Ton @2500 PSI	2 ½" x 28" x 28"	4" x 14"	20" x 20"	14	28"	2 ½"	15
DCP101S	10 Ton @ 1600 PSI	2 ½" x 22" x 28"	3 ¼" x 10"	16" x 22"	10"	20"	2"	7.5

Made In The USA ! Quality By American Tradesmen

S SERIES "DCP" 4-POST HYDRAULIC REGENERATIVE TRIM PRESS

QUALITY PRESSES WITH LONGEVITY !
WE HAVE BEEN MANUFACTURING NEW TRIM PRESSES SINCE 1968

Features S Series

- Platen machined from 1025 material
- Shut height adapters available
- 4-braid hydraulic hoses
- Safe, fully powered regenerative circuit
- Oil temperature & sight level gauges
- Cartridge valving manifold mounted
- Manual speed control
- Bolt on legs for shipping & rigging ease
- Ram speed 1 ft per second
- AB 500 processor
- Anti-drift cylinder seals.
- 5/8" t-slotted platens
- Solenoid indicator lights
- TEFC energy efficient pump motors
- Vickers double vane pump
- Chrome alloy tie bars
- Chrome plated trim cylinder piston rod
- One point tie bar lubrication
- **Operator safety pullouts with coincide anti-repeat**

Die Cast Press Mfg. Co., Inc.

Phone (269) 657-6060 - Fax (269) 657-9302



Options available for S Series presses:

- Air operated safety ratchet and palm buttons Air operated parts unloading shuttle
- Keyence light curtains
- Auxiliary hydraulic valve and electrics for secondary operations such as side trimming, punching and piercing.
- Auto tie bar lubrication systems